

PATENT APPLICATION
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

TITLE: HIGH RESOLUTION INK-JET
PRINTING ON EDIBLES AND PRODUCTS MADE

INVENTORS: Neil A. Willcocks
Thomas M. Collins
Arun Shastry
James M. Suttle and
Alfred V. Camporini

"Express Mail" mailing label number EK412632031US
Date of Deposit June 2, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to: Assistant Commissioner of Patents, Washington, D.C. 20231

Raymond B. Mandra
(Typed or printed name of person mailing paper or fee)

R B Mandra
(Signature of person mailing paper or fee)

09587108-060200

- 1 -

TITLE

**HIGH RESOLUTION INK-JET PRINTING ON EDIBLES AND
PRODUCTS MADE**

5

BACKGROUND OF THE INVENTION

Field of the Invention

- 10 The invention is directed to high resolution printing on edibles using an ink-jet printer and dispersed pigmented inks. The system provides for rapid turnaround from image input to printed edible product. Methods of printing, ink formulations suitable for use
- 15 with the methods, site-vending and e-commerce applications are all described herein, and are within the intended scope of the invention.

Description of the Related Art

- 20 Highly detailed images can be formed on chocolates using a pad printing process. In this process, the substrate is contacted with an inked pad having the image formed thereon. Sometimes, in order to prepare an image having greater resolution, the chocolate is
- 25 contacted repeatedly with the pad. An example of a pad

09587108.060200

printing process is described in CA 2,057,985. While, the pad printing process can deliver highly detailed images it cannot be adapted for rapid turnaround applications. Each requested change to an image
5 requires that a corresponding change be made to the printing pad or the manufacture of a new pad which means that pad printing will have a slow turnaround time. One object of the invention, therefore, is to provide for rapid turnaround printing of high
10 resolution images on edibles.

Ink-jet printing systems are generally of two types: continuous jet and drop-on-demand. In continuous jet ink-jet systems, ink is emitted in a continuous stream
15 under pressure through at least one nozzle. The stream is broken up into droplets at a fixed distance from the orifice. Typically, the ink droplets in continuous ink-jet systems are formed by a piezoelectric crystal, which is vibrated at controlled frequency adjacent to
20 the ink stream. To control the flow of ink droplets, these inks are charged (by addition of salts and other conductive agents) and relayed in accordance with digital data signals. The droplets are passed through an electrostatic field, which adjusts the trajectory of
25 each droplet. The droplets are either directed back to a gutter for recirculation or to a specific location on the substrate to create the desired character matrix.

In drop-on-demand systems, a droplet is expelled under
30 pressure from a valve directly to a position on the substrate in accordance with the digital data signals. A droplet is not formed or expelled unless it is to be

005537108.060200

jetted to the substrate. The formation of droplets in drop-on demand systems can either be achieved by a piezoelectric crystal (similar to continuous jet systems) or by a thermal (bubble-jet) technique. The latter technique involves formation of ink droplets by thermally heating ink in the cartridge reservoir thereby forcing ink to be expelled in an "on-demand" basis. Typically, drop-on-demand systems print at a slower rate than continuous jet systems (due to time required to make droplets on demand) but produce higher resolution images. However, some of the commercially available printhead units (for example, manufactured by Xaar, Trident and Picojet) achieve high throughput rates even with drop-on-demand systems by using their proprietary technologies. Also, since drop-on-demand systems require no ink recovery, charging, or deflection, these systems are simpler than the continuous stream systems.

Further, continuous jet ink-jet printing systems do not yield the same high resolution images that can be obtained with drop-on-demand ink-jet systems. A typical maximum resolution for a continuous jet printer image on an edible substrate using a single printhead and a single pass printing is about 70-90 dpi.

Published European Patent Application EP 705 890 A1 discloses an ink for use with a continuous ink jet printer. The ink comprises pigment, such as titanium dioxide; binder, such as shellac or poly(1-vinyl-2-pyrrolidone); and an aqueous carrier. The binder is apparently required to increase the compatibility of

005587108.060200

the inked image with the substrate in the continuous ink-jet environment contemplated.

Other methods of decorating edibles are known in the prior art. UK Patent GB 2,291,838 B describes a machine and method for printing on an edible substrate. This patent discloses a generic ink-jet/bubble-jet head assembly together with a stepping motor for moving the head assembly. A pump provides food coloring to the head assembly from ink reservoirs. A computer provides the instructions for printing on the edible substrate.

Food colorings which are dye-based systems behave differently than dispersed pigmented inks in an ink-jet environment, and exhibit profoundly different image characteristics on edible substrates. Dye-based inks possess limited opacity and therefore do not hide dark backgrounds colors, such as milk chocolate and dark chocolate surfaces. Also, dye-based inks are not available in all colors. For example, white ink is not available as a dye system but is available only as a pigmented (dispersed) system.

The examples of the prior art do not describe methods or systems to print high resolution images on edibles using an ink-jet printer and pigmented inks. There is also no description of a system or method wherein a consumer can participate in the selection and customization of an edible product with a high resolution image and subsequently receive the customized product in rapid fashion.

002090-30128560

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1A is a block diagram showing the elements of a system for preparing edibles having high resolution images ink-jet printed thereon.

Figure 1B is a block diagram of a manufacturing subsystem of the system of Figure 1A.

10

SUMMARY OF THE INVENTION

It is an object of the invention to provide a customizable process for preparing edibles having high resolution images that have been selected by a consumer ink-jet printed thereon according to the invention that comprises the steps of: selecting digital image information; processing the digital image information to form processed digital image information; ink-jet printing an image corresponding to the processed digital image information using dispersed pigmented ink; wherein said step of selecting digital image information is performed by an individual consumer.

The input of the individual consumer is a key component of the customizable process according to this embodiment of the invention. Rapid turnaround from the consumer's selection of digital image information to finished product having high resolution images printed thereon makes possible the consumer's involvement in the manufacture of personalized products.

09587103-060200

In preferred embodiments, the above system for preparing edibles having high-resolution, consumer selected images printed thereon, is embodied in connection with a rapid-turnaround site-vending or e-commerce application. In these embodiments, the consumer selects digital image information, at a vending site or over the internet, for example. The information is processed, remotely or on-site, and printed onto an edible substrate with an ink-jet printer using the dispersed pigment food grade inks of the invention. The entire process is accomplished according to consumer selections with rapid turnaround. In some embodiments, the turnaround can be on an as-you-wait basis.

It is a further object of the invention to provide a process for printing high resolution images on an edible substrate comprising the steps of: (a) providing digital image information; (b) processing the digital image information to prepare processed digital image information; and (c) printing an image from the processed digital image information on an edible substrate with a drop on demand ink-jet printer using dispersed pigment food-grade ink to obtain a printed image having resolution greater than 200 dpi.

Significantly, the image resolution (as measured in dots per square inch, (dpi)) achieved using the process of this invention may be obtained even using a single printhead and single pass printing. Of course, the invention set forth herein is not limited to a single printhead or single pass printing, but also includes

002030-80178560

the use of multiple printheads and/or multiple pass printing.

It is a further object of the invention to provide a
5 system for preparing edibles having high-resolution,
consumer-selected, dispersed pigmented ink images
printed thereon with an ink-jet printer, comprising: a
digital image information selection device in
communication with an image processor for producing
10 processed digital image information and an ink-jet
printer adapted to print a high resolution image
corresponding to said processed digital image
information on an edible substrate.

15 It is also an object of the invention to provide novel
edible dispersed pigmented ink compositions which can
be used in drop on demand ink jet systems to deliver
high resolution images.

20 Novel edible, ink-jettable ink compositions according
to the invention comprise: a food-grade white pigment,
a dispersant, an alcohol, and water.

In a particular embodiment, the present invention
25 comprises a food-grade, drop-on-demand ink jettable ink
consisting essentially of: titanium dioxide, glycerine
and/or propylene glycol and/or polypropylene glycols, a
lower alcohol, water, and optionally a surfactant. In
a preferred embodiment, the ink is substantially free
30 of binder.

002090" 80728560

It is also an object of the invention to provide high resolution images on edible substrates with dispersed pigmented inks printed with drop-on demand ink-jet technology. Particularly preferred embodiments
5 according to the invention include white ink images having a resolution greater than 200 dpi, and more preferably between 300 and 1200 dpi, printed with drop-on demand ink-jet technology on chocolate substrates.

10 In a particular embodiment, novel high resolution printed edible products are described, wherein a printed image is printed on a surface with localized three dimensional (3-D) features, for example an irregular or uneven surface.

15 It is a further object of the invention to provide a computer-readable medium storing executable code adapted to control a server computer on a network to perform a method for facilitating custom manufacturing
20 of a decorated edible item on the basis of instructions of a user. The method includes communicating over the network with a client computer of the user, receiving over the network, from the client computer, image information submitted to the client computer by the
25 user, and communicating the received image information to an ink-jet printer to cause printing on an edible item of a high quality image that corresponds with the received image information.

09587108.060200

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An important motivation behind the use of ink jet printing is that this type of printing allows rapid
5 turnaround from the selection of an image to the printing of edibles bearing the selected image. The rapid turnaround enabled by the use of ink-jet printing (as opposed to pad printing) permits a consumer to dictate the steps of digital image information
10 selection and image processing. The rapid-turnaround, consumer-centered approach to printing on edibles permits the introduction of applications heretofore not deemed possible, or if possible, impractical.

15 In some embodiments, the present invention comprises a system for preparing edibles having high-resolution, consumer-selected and/or consumer-provided images printed thereon. The consumer's involvement in the preparation of an individualized edible is a key
20 component of these embodiments of the invention. Thus, in the system, a digital image selection device is consumer-driven.

The process for printing high resolution images on an
25 edible substrate according to the invention comprises, in the first instance, the step of providing digital image information. The source of the digital image information is not particularly limited. Digital image information for use with the printing process of the
30 present invention may be in the form of an electronic file (on disk or otherwise), or may be transmitted from a source. Providing digital image information may be

09587108.060200

accomplished, for example, with a keyboard, a digital camera, a scanner, a digital video camera, or the image may be provided in pre-recorded image format.

Presently available technology includes many sources of
5 digital image information that would be known to those of ordinary skill in the art, and which could be readily used in the step of providing digital image information.

10 Digital information must be in communication with the image processor. Communication may be effected over the Internet, by a computer, through computer cables, wiring, fiber optic cabling, or other means through which digital image information can be transmitted.
15 Specifically contemplated herein is an embodiment wherein a digital image information selection device is incorporated with the image processor. For example, a digital camera typically includes options for processing an image. In this situation, the digital
20 image information selection device is said to be in communication with the image processor. Likewise, when digital image information is captured by a digital image information selection device and placed on a storage medium, and thereafter the digital image
25 information is loaded into a software package for processing the image, the digital image information selection device is said to be in communication with the image processor. Similarly, when digital image information is received over the Internet by the server
30 functionality of the present invention, this will constitute the communication. The structural details

09587108.060200

of these programs or communicating devices are well known.

00587108-060200
In preferred embodiments, the digital image information
5 is provided under the direction or control of
individual consumers. A site-vending application can
include an area, such as a kiosk, where the consumer is
provided with a digital camera, keyboard, computer
terminal or the like to prepare individualized digital
10 image information. Of course, any type of device
capable of providing digital image information, such as
personalized messages, sentiments or a clip-art image
selected by the consumer from a library of such images
may be used. The digital image information may be then
15 processed at the site and printed on an edible
substrate, such as chocolate, on an as-you-wait basis.

In a preferred embodiment, consumers provide
individualized digital image information at a computer
20 which is linked on-line to the internet. In either the
site vending or internet embodiments of the present
invention, there is rapid turnaround between the
consumer's selection of digital information and
obtaining edibles printed with the selected images.

25

In a particularly preferred embodiment of the present
invention, the system utilizes a wide area network
(WAN) such as the Internet to receive custom orders
from consumers for designs to be printed on the edible
30 items. The system preferably includes an Internet
(TCP/IP compliant) server that interacts with consumer
client computers using the client computer's graphical

002090" 807.8560

user interface (GUI). The interface with the consumer preferably allows the consumers to interactively peruse options for decoration of edibles, and more preferably, the ability to preview what the final product will look
5 like. The above functionality is preferably achieved using a combination of server side applications, such as common gateway interface programs (CGI), for allowing the server to accept search terms and interface with databases, and client side applets, such
10 as Java applets, or the like, which execute in client browser software.

A preferred implementation of the consumer customized manufacturing system of this present invention is
15 illustrated in block diagram form in Figure 1A. In that figure, consumers operating client computers 1 are connected to a wide area network (WAN) such as the Internet. Such connection can be direct or via an Internet service provider (not shown). The client
20 computers 1 each preferably include communications hardware and an operating system with graphical user interface (GUI) functionality to allow for interface with the Internet. Each client computer preferably has graphical World Wide Web (Web) browser software, such
25 as Netscape Navigator or Microsoft Internet Explorer, loaded thereon operable to read and send Hypertext Markup Language (HTML) forms from and to an Hypertext Transport Protocol (HTTP) server on the Web. The client computer 1 preferably is operable to act as a
30 virtual machine to run Java applets, or the like, downloaded by the browser from the server.

Server/host computer system 2 receives information from consumer client computers 1 over the Internet. The server/host computer system 2 preferably includes hardware, HTTP compliant software, an operating system
5 and common gateway interface (CGI) software for interfacing with input queries and sources of data.

Manufacturing subsystem 3, to be described in more detail below, includes the hardware and software
10 necessary to interface with the server/host computer system 2 and to use the input information to custom manufacture decorated edible items. On site data entry 4 allows on site entry by consumers of custom orders as an alternative to receipt of this information over the
15 Internet.

A preferred implementation of manufacturing subsystem 3 is illustrated in block diagram form in Figure 1B. Central Processing Unit (CPU) 10 is a computer having
20 the functionality to run software programs, communicate with outside sources of data, and control peripheral devices. Preferably, the CPU 10 is operable to configure data for graphical display from input data received from server/host computer system 2 and on site
25 data entry 4, as well as from graphical data files stored in storage device 30, or RAM 20. A user can interface with the CPU 10 using keyboard 40 and/or mouse 45, preferably using a GUI operating system. Printer 60 is used to decorate the edible items under
30 the control of the CPU 10 based upon the graphical data. Prior to printing, the graphical data may be subjected to modification by the user of the CPU 10, if

09587108-060200

necessary, by using the keyboard 40 and/or mouse 45 in conjunction with the GUI.

In operation, in the Internet implementation, a
5 consumer typically would type in a Uniform Resource
Locator (URL) of the server/host computer system 2 and
receive from the server/host computer system 2 an
interactive form, such as an HTML document, as well as
any Java applets, or the like, necessary to allow the
10 consumer to view and submit his or her options for
customizing the decoration of the edible items. The
applets and CGI programs do verifications to ensure,
for example, the consumer does not chose too large a
decoration for the edible. Assuming the consumer
15 request is within appropriate limits, the server acts
as an intermediary to pass the requested information
along to the manufacturing subsystem for actual
printing under the control of CPU 10.

20 An example of the integrated system of the present
invention includes a method in which the consumer
selects digital image information while on-line. The
consumer selects digital image information by entering
from the keyboard, selecting from a library of images,
25 inputting a digital photograph, remotely controlling
the taking of a live digital photograph or video image,
or other mode available on-line. The consumer then
communicates, by conventional Internet interfacing
techniques, the selected digital image information
30 through server/host computer system 2, to remote image
processing functionality operating in CPU 10.

00587108-060200

Alternatively, the consumer may simply invoke an image processor while on-line and communicate, in real time, the digital image information to a program for processing an image. Thus, the step of processing the digital image information to produce processed digital image information does not have to be done remotely, but may be accomplished while the consumer is on-line, and under the interactive, real time supervision of the consumer. After the digital image information has been communicated to the image processing functionality of CPU 10, and processed digital image information has been produced, the processed digital image information is transmitted to an ink-jet printer for printing on an edible substrate.

The server/host computer system 2 and on site data entry 4, preferably, in addition to communicating to the manufacturing subsystem, communicates with a financial computer of the system to utilize input customer credit card information or the like for payment for the custom decorated edible items. Further, the server/host computer system 2 and on site data entry 4, preferably, in addition to communicating to the manufacturing subsystem and the financial computer of the system, also communicates with an inventory management computer system to coordinate the rapid fulfillment of the customer order through timely shipment of the customized product.

In some circumstances, the consumer may be involved in the step of processing the digital image information by changing visual parameters, such as colors, tones,

09587108.060200

brightness, contrast, or the size and aspect ratio of the image, or by cutting-and-pasting or merging images, and the like.

5 If the digital image information is provided over the Internet, software, in the form of Java applets, or the like, for processing the image on the consumer's client computer can be provided on-line. Alternatively, the consumer may be provided with an image processor for
10 digitally processing the image at the site where the digital image information is provided, for example at on-site data entry 4. Software packages for processing digital image information are known, and the invention is not particularly limited in this regard.

15 An image processor is, generally speaking, a software package that permits sophisticated alteration of digital image information. As indicated above such programs are known in the art. Commercially available
20 programs that may serve as image processors include, without limitation, Adobe Photoshop and Microsoft Photo Editor. Less involved image processors are contemplated, and might include, without limitation, standard picture controls available on a digital still
25 camera or digital video camera.

Certain sub-steps involved in the step of processing the digital image information may be "invisible" to the consumer, notwithstanding how the image is provided.
30 By "invisible" in this context is meant that certain sub-steps of image processing will likely take place without the direct involvement of the consumer. This

09587108.060200

is because certain image processing steps are known from experience to be suitable for particular substrates, such as taking the negative of an image to be printed in white on chocolate, and these steps would not be expected to be readily apparent to the consumer. Likewise, in some instances it may be desirable to resolve the digital image information into a series of images that are printed on top of one another to create a higher resolution image. This sub-step of resolving the image into a series of image layers is the type of sub-step that might be "invisible" to the consumer.

In a preferred embodiment[s], the digital information selection device is provided at the same site where the image processor and the ink-jet printer are located. This type of embodiment can be referred to as a site-vending application, where the consumer selects digital image information, optionally participates in the processing of the digital image, and then waits while an edible bearing the selected high-resolution image is produced. Of course, the turnaround need not be on an as-you-wait basis. The consumer may place an order and return for it. Nevertheless, rapid turnaround of individually customized edibles is contemplated using the systems, processes and inks according to the invention.

In a particularly preferred embodiment, the digital information selection device, image processor, and the ink-jet printer are integrated in a single portable apparatus. For example, a portable apparatus would find application with photographers taking photographs

09587108-060200

at special occasions such as weddings, reunions, etc..
The rapid turnaround capability of the invention would
allow the capturing of images of the participants of
the occasion and the delivery of confectionery products
5 with their images while they are still at the occasion.

While the preferred embodiments have been described
above in relation to digital image selection via
software running on a consumer's client computer 1, or
10 via on-site data entry 4, the digital image information
selection device of the present invention is not
limited to the illustrated embodiments. Examples of
such selection devices for use on-site may include a
keyboard or computer terminal, a live video camera
15 image acquisition device, a digital still camera image
acquisition device, a scanner, a reader for reading
digital information, or any other type of device for
supplying digital image information known in the art.

20 The step of printing an image on an edible substrate
according to the invention utilizes printer 60, an
apparatus that may be described as a conventional ink-
jet printing apparatus modified to operate using the
edible ink of this invention and modified to print on
25 the edible substrates of the invention. The preferred
ink-jet printing apparatus is a drop-on-demand ink-jet
printing apparatus, comprising a cartridge for holding
ink which is integrated with a print head for printing
on the substrate. The apparatus comprises a driver for
30 driving the print head according to instructions
corresponding to the processed digital image
information received. The apparatus typically

002090.20128560

comprises a conveyer for causing relative motion between the substrate and the print-head.

Once the digital image information has been provided,
5 the image is processed to prepare processed digital image information. This information is then communicated to the printer in appropriate form to enable the printer to produce the high resolution printed image on the edible product. Of course, edible
10 substrates come in a variety of colors, and printed images will have to be processed at least so that a printed image has the appropriate intensity and contrast for the background color of the substrate. In a preferred embodiment, the printed image comprises
15 white ink, and the substrate is chocolate. In this situation, the step of processing an image, for example a digital photograph or the like, will involve taking the "negative" of the digital image information, and enhancing image brightness and contrast prior to
20 printing. This can be accomplished, for example, using an image processor such as Adobe Photoshop.

Dispersed pigmented white ink, which is discussed in more detail below, is provided to the "black" reservoir
25 or cartridge of a black-only ink-jet printer. Obviously, if a non-white single color image is desired, a pigment based ink containing a dye would be provided to the "black" reservoir of the cartridge. If a printer with a color ink cartridge is utilized, white
30 ink will be provided to the black reservoir and "colored" pigment based inks will be provided to the remaining reservoirs. The particular arrangement of

002090.80128560

the reservoirs is not particularly critical. It is
advisable to sonicate (i.e. ultrasonically mix) the
cartridge to effect dispersion of the pigments in the
ink prior to printing and intermittently to prevent the
5 nozzle from becoming clogged.

Once the printer is loaded with ink, the edible
substrate is held and conveyed past the print-head (or
vice versa). The edible substrate is not particularly
10 limited. In a preferred embodiment, the substrate is a
confectionery product. The substrate may be for
example, chocolate, cookies, M&M@s-type candy or other
sugar shell candy, or hard candy, jellybeans, starch-
based, savory snacks, and gelatin-based gummi and soft
15 candies. Even ice creams and pet food are within the
scope of the invention. In a preferred embodiment, the
substrate is a predominantly planar chocolate tablet.

Other embodiments of image processing according to the
20 invention include, controlling the intensity of the
brightest area of an image, electronically separating
an image such that it can be printed in multiple
applications of ink (i.e., multi-pass through printer),
brightness equalization across the printed area, and
25 sectional control of image brightness and contrast.

Printing on a substrate such as chocolate presents
special challenges in obtaining a high quality high
resolution image. The use of techniques described
30 above have been discovered to address many of the
challenges. For example, when printing using ink-jet
technology onto chocolate, the compatibility of the ink

09587108 "060200

with the surface is critical. The surface chemistry of the chocolate surface and that of the ink will determine the behavior to the ink droplets once they have been jetted onto the surface. By controlling the maximum level of brightness for an image, it is possible to ensure that too much ink is not jetted into a given section of a printed image. When this occurs, the ink droplets may tend to coalesce into larger droplets before the ink has had sufficient time to completely dry. This leads to a loss of resolution for the affected section of the image.

Another embodiment is to "separate the image into layers" such that the printing of the complete image is completed by multiple applications of ink. This allows sufficient time for the successive ink applications to dry before another application is made. This allows a larger total application of ink and thus brighter images while avoiding loss or resolution due to coalescence of printed droplets.

Another embodiment utilizes an approach of brightness equalization across the printed area. By adjusting the contrast and shading of the light and dark areas of an image, it is possible to enhance the overall quality of the image on a chocolate surface. This technique tends to minimize extremes of darkness or brightness and results in an improved image quality for images with very severe contrasts.

30

Another embodiment is to control the brightness of an image in certain sections of an image rather than of

09537103-060200

the image as a whole. Here again, the image quality and resolution will be enhanced by avoiding coalescence problems in very bright areas of the image.

- 5 These techniques will generally allow more difficult images to be printed onto chocolate in a manner to deliver a high quality, high resolution image. This is particularly valuable for images with intricate patterns which otherwise might produce lower quality or
10 lower resolution images.

As mentioned earlier, the surface chemistry of the ink and the chocolate surface play a critical role in determining the final image quality and resolution.

- 15 Other embodiments according to the invention which can have advantageous effect on image quality include, controlling the surface energy of the chocolate by changing the temperature of the substrate of the ink, using a stream of dry gas to assist the rapid drying of
20 ink droplets on the surface of the chocolate and applying coatings to the chocolate to enhance the compatibility of the chocolate to the ink.

- Temperature modulation will affect the surface energy
25 properties of the ink and chocolate with lower temperatures lowering surface energy and reducing the tendency of an ink to spread across the chocolate surface. Applying very low humidity gas or air will enhance the drying rate of the ink droplets and can be
30 employed effectively with the multi-pass printing embodiment discussed above. Temperature modulation of the ink cartridge can also be advantageously used to

09587108-060200

modify and or control ink rheology to maximize printing performance.

09587108.060200

In some instances it may be desirable to enhance the compatibility of the surface of the confection by depositing a thin layer of an edible binder or other compatibility-enhancing component prior to the step of printing the image. Water-based glazes containing gums and/or corn syrups and/or oils, and/or acids and/or sugars and/or starches and/or low-carbon alcohols and/or shellacs and/or other resins provide sufficient chocolate surface modification to allow high-resolution images to be printed using the above mentioned inks. Solvent based glazes may also be useful. Commercial names of exemplary water-based glazes include, without limitation, commercially available Capol 140, Capol 120, Capol 153D, Capol 149 products, available from Centerchem Foods, Stamford, Connecticut. These ingredients, besides providing compatibility of inks to chocolate surface, provide a unique glazed appearance to the printed images. Other components which may be coated on the surface of an edible substrate prior to printing include surfactants, antibloom agents, micronutrients and flavor enhancers.

25

An example of a surfactant than can improve the compatibility of the ink with a chocolate surface is Adsurf 456K. Application of a thin layer improves the image quality and resolution significantly. Another embodiment of the invention involves the application of more than one surface pre-treatment layer prior to ink-jet printing. Among surface pre-treatments, the

09587108-060200

application of a Capol glaze to the chocolate surface provided the best surface in terms of ink compatibility. However, it is very difficult to deliver a uniform layer of the Capol glaze to the chocolate surface. Surprisingly, it has been found that combining a first pre-treatment application of a surfactant, such as Adsurf 456K, followed by a second application of Capol provides a very significantly improved surface for ink-jet printing. The sequential application of this multi-layer pre-treatment, using a foam brush, provides a smooth highly compatible surface for edible pigmented ink-jet ink. This delivers a very superior image quality and resolution. This surface is also much less prone to ink droplet coalescence problems.

The image enhancement techniques discussed in application to chocolate products are not limited to these products but are generally applicable in principle to other edible substrates.

The present invention also provides for novel high resolution printed edibles wherein the edibles have a substantially planar or substantially non-planar shape. As used herein, substantially planar includes, for example, a chocolate tablet, while substantially non-planar includes, without limitation, an interior or exterior surface having curvature, such as an egg. The novel printed edible is printed on at least one surface having localized 3-D features if substantially planar. If substantially non-planar, the printed surface may be on localized 3-D features. Localized 3-D features can

include, without limitation, uneven or irregular surfaces, such as grooves, ridges, pinholes, and the like, as well as embossed or molded designs in the edible substrate.

5

In preferred embodiments, the edible may be moved or rotated in an appropriate manner to transiently bring a non-planar surface into correct position and distance for printing below or aside a drop on demand printer head. For example, high resolution images can be printed on a Chocolate Easter Egg by a system which holds the egg and moves it past a horizontally mounted printer head in rotational manner to present an arc of the egg surface for printing. In a particularly preferred embodiment the system will control the edible in such a manner as to transiently maintain the non-planar surface being printed at a perpendicular angle to the print head.

20 In another preferred embodiment, it is possible to print the interior surface of a $\frac{1}{2}$ egg or $\frac{1}{2}$ ball shaped product produced by shell molding and which is ultimately joined to another half to yield a hollow molded edible product.

25

In formulating an ink composition that is edible, ink-jettable, and which provides an acceptable high-resolution high quality image, several competing factors need to be addressed. Generally speaking, a dye-based ink will not provide an acceptably high-quality image on most edible substrates, such as dark surfaced substrates and/or non-porous materials, due to

09587108.060200

poor image contrast and therefore, the invention is directed primarily to dispersed pigmented inks.

The edible dispersed pigmented inks of the invention
5 are generally prepared in the following manner. First,
the pigment dispersion is prepared by thoroughly mixing
an edible pigment with a suitable edible dispersant.
Next, the pigment dispersion is carefully diluted or
let-down using an edible carrier fluid to produce the
10 dispersed pigmented ink. As the inks of the invention
are water based, the carrier fluid will typically be
comprised of water and an edible alcohol. Optionally,
an edible surfactant may be added to the ink, either at
the dispersion step or later.

15 In preparing dispersed pigmented inks, enough pigment
must be used in the formulation to lend sufficient
opacity to the printed image, and it must be ensured
that the pigment is uniformly dispersed in the ink. In
20 the production of a white ink, at least about 3 weight
percent of white pigment is required to provide
sufficient opacity and dispersivity in the ink. At the
same time, if too much pigment is used, the resulting
ink will tend to clog the nozzle orifices of an ink-jet
25 printer, particularly a drop-on-demand ink-jet printer.
Additionally, at high pigment levels, the ink viscosity
is increased to levels such that flowability of ink
within the ink cartridge and nozzles is restricted.
Thus, an upper compositional limit for pigment in the
30 edible ink composition according to the invention is
about 55 weight percent. Where titanium dioxide is
used as the pigment the desirable range is between 10-

09587108.060200

45 weight percent and the most preferred amount of pigment to use is about 13-35 weight percent. As used herein "weight percent" means percent by weight with respect to the weight of the ink composition, unless
5 specifically stated otherwise.

Powdered materials that may be used as a pigment in the edible ink composition according to the invention include, but are not limited to: titanium dioxide,
10 aluminum hydroxide, calcium carbonate, sucrose, and talc. Titanium dioxide is most preferred.

For use with a drop-on-demand ink-jet system, the pigment particles should have a particle size between
15 about 0.1 and about 1.5 microns. The preferred titanium dioxide pigments have an average particle size in the range of about 0.2 to about 0.5 microns, with an average particle size of 0.3 microns being the most preferred particle size.

20 To prepare an ink composition according to one embodiment of the invention, first the pigments are dispersed in a dispersant to produce the pigment dispersion. Suitable dispersants include, without
25 limitation, glycerine and/or propylene glycol and/or polypropylene glycol and other polyglycerols and polyols. A suitable amount of glycerine and/or propylene glycol and/or polypropylene glycol and other polyglycerols and polyols will serve to adequately
30 disperse the pigment while making sure that fluid properties of the finished ink are not adversely affected. The preferred range of glycerine and/or

09587108-060200

propylene glycol and/or polypropylene glycol and other polyglycerols and polyols in the finished ink is between about 1 percent and about 48 percent.

5 According to the invention, other dispersants may also be used beyond those described above. The essential requirements being that the dispersant is edible and effectively disperses the pigment and does not lead to clogging problems of the printer nozzle orifice. For
10 example, water based carbohydrate and or protein solutions may also be used to disperse the pigment. It is also possible to use combinations of dispersants. It is also possible to use salts or other compounds to charge the pigmented particles and therefore help
15 disperse the pigments.

The ink compositions according to the invention are typically water-based. Preferably, water comprises between about 30 and about 75 weight percent of the
20 final ink composition. In yet another embodiment, the ink composition may also be substantially free of water.

An alcohol is added to the ink composition as part of
25 the carrier so that the image will dry quickly once printed. Any alcohol suitable for use with an edible composition that will increase the volatility, and therefore the drying speed, of the ink may be used. Lower alcohols, and in particular ethanol and isopropyl
30 alcohol, are preferred. Enough alcohol must be used to ensure that the ink will dry quickly, but not so much that the flashpoint of the ink composition is reduced

002090 80178560

to a dangerous level. The preferred range of alcohol is between about 5 and about 70 weight percent of the final ink composition. A more preferred range is between about 7 weight percent and about 45 weight percent. The most preferred range of alcohol is between about 10 weight percent and about 25 weight percent with respect to the final ink composition.

The edible ink composition according to the invention may also comprise a surfactant to improve the compatibility of the ink with the surface of the chocolate. The surfactants that may be used in the ink of this invention include, for example, anionic surfactants, cationic surfactants and amphoteric surfactants. Of course, the surfactant used must be edible in the amounts used. The most preferred surfactants are polyglycerol oleates, monostearates, polysorbates, mono and diglycerides, commercially available under the tradenames of Adsurf 456K, Tween 60, Tween 80, Span 60, and Span 80, Myverol and Myvecet. Generally, a surfactant will be present in amounts less than about 1.0 weight percent. Most preferably, the surfactant will be present in an amount between about 0.001 and about 0.5 weight percent (based on final ink-formulation).

As the composition is an edible composition, a simple composition is preferred. The edible ink according to preferred embodiments of the invention is substantially free of shellac or polymeric binder. It has surprisingly been found that the composition as recited above, with the optional addition of a small amount of

09587108.060200

surfactant is sufficient to obtain good image durability and compatibility of the image with a chocolate substrate.

5 Other ingredients may be added to the ink including, but not limited to flavor enhancers and micronutrients. Such components, frequently added to the surfaces of edibles, particularly confections, would be known to one of ordinary skill in the art and include, without
10 limitation, mint, fruit and vegetable oils, herbal extracts, cinnamon and coffee flavorings, vanillin and vanilla extracts (natural and artificial), malt flavors, vitamins, minerals, plant phytochemicals, anthocyanins, etc. Although not particularly limited
15 in this regard, it is contemplated that these flavor enhancers and micronutrients may be present in an amount between about 0.01 weight percent and about 5 weight percent. Further, the flavor enhancers and micronutrients added according to the invention may be
20 suitable for either human or animal palatability and health.

As noted earlier, the use of dyes on most edible substrates does not produce a satisfactory image.
25 However, the ink composition of the present invention may include dyes in addition to the pigment. It has surprisingly been found that combining dyes with titanium dioxide pigment yields colored inks having greater intensity and opacity than when the food dyes
30 are used as sole colorants in an ink formulation. It is also within the scope of the invention to use lakes

002090" 80128560

in combination with titanium dioxide pigment in a colored ink composition.

Generally, if dyes are present, the amount will range
5 between about 0.5 and 5.0 weight percent with respect
to the edible ink composition. Water based dyes such
as F D & C approved colors, natural colorants and mica-
based metallic color pigments are preferred for use
with the edible inks of the invention.

10

A consumer-driven, customizable process for producing
edibles having individualized, high-resolution images
printed thereon is made possible by the invention. The
full scope of the invention is set forth in the
15 appended claims, and includes equivalents and
alternatives of the disclosed inks, processes, and
systems and obvious variants thereof.

09587108-060200